

AquFlow

S4000 PERFORMANCE TABLE

Model No.	Capacity GPH (LPH)	Pressure PSIG (bars)	Speed (SPM)	Plunger Diameter	Connection (NPT)
GNIT 0744-0X01A	22.6 (85.5)	3,500 (241)	44	7/8"	1-1/4"
GNIT 0770-0X01A	36.0 (136.3)	3,500 (241)	70	7/8"	1-1/4"
GNIT 0788-0X01A	45.0 (170.3)	3,500 (241)	88	7/8"	1-1/4"
GNIT 0714-0X01A	72.0 (272.5)	3,500 (241)	140	7/8"	1-1/4"
GNIT 0944-0X01A	38.5 (145.7)	2,000 (138)	44	1-1/8"	1-1/4"
GNIT 0970-0X01A	61.5 (232.8)	2,000 (138)	70	1-1/8"	1-1/4"
GNIT 0988-0X01A	77.0 (291.5)	2,000 (138)	88	1-1/8"	1-1/4"
GNIT 0914-0X01A	123 (465.6)	2,000 (138)	140	1-1/8"	1-1/4"
GNIT 1344-0X01F	79.5 (300.9)	1,000 (69)	44	1-9/16"	2-1/2"
GNIT 1370-0X01F	126 (477.0)	1,000 (69)	70	1-9/16"	2-1/2"
GNIT 1388-0X01F	159 (601.9)	1,000 (69)	88	1-9/16"	2-1/2"
GNIT 1314-0X01F	253 (957.7)	1,000 (69)	140	1-9/16"	2-1/2"
GNIT 2444-0X01F	210 (794.9)	370 (26)	44	2-1/2"	2-1/2"
GNIT 2470-0X01F	335 (1,268.1)	370 (26)	70	2-1/2"	2-1/2"
GNIT 2488-0X01F	421 (1,593.7)	370 (26)	88	2-1/2"	2-1/2"
GNIT 2414-0X01F	671 (2,540.0)	370 (26)	140	2-1/2"	2-1/2"
GNIT 0744-0X01H	304 (1,150.8)	295 (20)	44	3"	4"
GNIT 0770-0X01H	485 (1,835.9)	295 (20)	70	3"	4"
GNIT 0788-0X01H	609 (2,305.3)	295 (20)	88	3"	4"
GNIT 0714-0X01H	970 (3,671.8)	295 (20)	140	3"	4"
GNIT 0744-0X01H	554 (2,097.1)	160 (11)	44	4"	4"
GNIT 0770-0X01H	882 (3,338.7)	160 (11)	70	4"	4"
GNIT 0788-0X01H	1,109 (4,198.0)	160 (11)	88	4"	4"
GNIT 0714-0X01H	1,765 (6,681.2)	160 (11)	140	4"	4"

